

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1  
Revision Date 10/07/2003

Page 1 of 6  
Print Date 11/24/2003

**1. PRODUCT AND COMPANY IDENTIFICATION**

**POLYONE CORPORATION**  
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship (314) 771-1800  
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : XDR52241A EXPERIMENTAL QUANTUM BASE  
Product code : FO20006563  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Components	CAS-No.	Weight%
Calcium carbonate	471-34-1	10- 30

**3. HAZARD IDENTIFICATION**

**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

**POTENTIAL HEALTH EFFECTS**

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

**Acute exposure**

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.  
Ingestion : May be harmful if swallowed.  
Eyes : May cause eye/skin irritation.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1

Revision Date 10/07/2003

Page 2 of 6

Print Date 11/24/2003

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

**Flashpoint** : No data available

**Flammable Limits**  
Upper explosion limit : No data available  
Lower explosion limit : No data available

**Autoignition temperature** : Not applicable

**Suitable extinguishing media** : Carbon dioxide blanket, water spray, dry powder, foam

**Special Fire Fighting Procedures** : Full face self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

**Methods for cleaning up** : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

**Handling** : Heat only in areas with appropriate exhaust ventilation. Processing

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1  
 Revision Date 10/07/2003

Page 3 of 6  
 Print Date 11/24/2003

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : safety glasses with side-shields

Hand protection : protective gloves

Skin and body protection : long sleeved clothing

Additional Protective Measures : safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5mg/m <sup>3</sup>	PEL:	Respirable fraction.	OSHA Z1
	15mg/m <sup>3</sup>	PEL:	Total dust.	OSHA Z1
	10mg/m <sup>3</sup>	Time Weighted Average (TWA):		ACGIH

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: liquid	Evaporation rate	: Not established
Appearance	: Viscous, liquid	Specific Gravity	: Not determined
Color	: NO PIGMENT	Bulk density	: Not applicable
Odor	: Very faint	Vapor pressure	: Not determined
Melting point/range	: Not applicable	Vapour density	: Not determined
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Immiscible		

**10. STABILITY AND REACTIVITY**

Stability : Stable.

Hazardous Polymerization : Will not occur.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1  
Revision Date 10/07/2003

Page 4 of 6  
Print Date 11/24/2003

- Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
- Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177°C (350°F), after 10 minutes at 204°C (400°F), and within 5 minutes at 232°C (450°F).

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin .

LC50/LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1  
Revision Date 10/07/2003

Page 5 of 6  
Print Date 11/24/2003

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Refertot specific regulation.  
ICAO/IATA (air) : Refertot specific regulation.  
IMO/IMDG (maritime) : Refertot specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : This product does not contain a substance listed by California Prop 65.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : Not controlled.

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**XDR52241A EXPERIMENTAL QUANTUM BASE**

Version Number 1.1  
Revision Date 10/07/2003

Page 6 of 6  
Print Date 11/24/2003

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.